

RECEIVED

JUN 24 1950

AREA 640 ACRES
LOCATE WELL CORRECTLY

State: LA
(Law)

Elevation above sea level at Top of Tubing Head.....3682..... The information given is to be kept confidential until
..... 19.....

No. 3, from.....to..... No. 6, from.....to.....

No. 4, from.....to.....feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	28	Used	739'	Float			Surface
5-1/2"	15.5#	New	6363'	Float			Oil String

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	739'	300	Pump - Plug		
7-7/8"	5-1/2"	6363'	162 Units HTS 400	Pump - Plug		
			150 sks. incore 1/2 gal.			

...Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6435 feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing.....**6-18-60**....., 19.....

OIL WELL: The production during the first 24 hours was.....672.....barrels of liquid of which.....99.8.....% was
was oil;0.....% was emulsion;0.....% water; and......2.....% was sediment. A.P.I.
Gravity.....42.8.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers..... 859	T. McKee.....	T. Menefee.....
T. Queen..... 1445	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg..... 1866	T. Gr. Wash.....	T. Mancos.....
T. San Andres..... 2184	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo..... 5997	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation
0	568'	568'	Red bed and Gyp.
568'	966'	398'	Anhy. and Gyp.
966'	2089'	1123'	Anhy. and Dolo.
2089'	3912'	1823'	Dolo. and Chert
3912'	4073'	161'	Lime and Dolo.
4073'	6023'	1950'	Chert and Dolo.
6023'	6435'	412'	Lime

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator.....**Hondo Oil & Gas Company**

Address.....**Box 125, Artesia, New Mexico**

Name..... **A. J. Deans**

Position or Title..... **Dist. Prod. Supt.**