

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-01558

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:
Empire Abo Unit "B"

8. Well No. B-40

9. Pool name or Wildcat
Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

B-P America

3. Address of Operator

P.O. Box 1089 Eunice, New Mexico 88231

4. Well Location

Unit Letter _____ P: 2310 feet from the _____ North _____ line and _____ 660 feet from the _____ East _____ line

Section 26 Township 17S Range 28E NMPM Eddy County NM

Elevation (Show whether DR, RKB, RT, GR, etc.)
KB 10'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.
PROCEDURE TO P&A. NO UP HOLE POTENTIAL

- 9-25-78 - Records indicate 5 1/2" csg. was circulated to the surface with 2910 sxs. cmt. to shut off water flow.
- Well has 4 sets of squeeze holes and 5 CR's are still in hole.
- Wireline survey on 10-14-92 indicates TOC inside 5 1/2" csg. @ 97'.
- Discussed well with NMOCD representative, Mr. Van Barton. He has agreed that all that is required to finish plugging the well is a cmt. plug in the top of the 5 1/2" csg.

PROCEDURE: (1) Dig out & remove tbq. head. Fill To
(2) Mix & pour sufficient amt. of cmt. to cap 5 1/2" csg. at the surface.
(3) Cut off well head & anchors 3' BGL. Clean up location. Set Dry Hole Marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kellie D. Apparrish TITLE Asst. Admin. Asst. DATE 07.22.02

Type or print name Kellie D. Apparrish Telephone No. 505.394.1649
(This space for State use)

APPROVED BY [Signature] TITLE Wild Sup ID DATE JUL 30 2002

Conditions of approval, if any:

Notify OCD 24 hrs. prior to any work done