

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR ~~CEMENTING~~ <sup>plugging</sup> OF WELLS

Operator <u>John Gallagher</u>		Lease <u>Dell Lake</u>		Well # <u>7</u>	
Location of Well	Unit <u>D</u>	Section <u>30</u>	Township <u>17</u>	Range <u>25</u>	County <u>FDDY</u>
Drilling Contractor <u>Blackie L A-1</u>	Type of Equipment <u>PULLING UNIT</u>				
<u>APPROVED CASING PROGRAM</u> <sup>106' plugging</sup>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	<u>7"</u>		<u>USED</u>	<u>396</u>	<u>30</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole \_\_\_\_\_ Size of Casing \_\_\_\_\_ Sacks cement required \_\_\_\_\_

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded \_\_\_\_\_

TD of hole 510 Set \_\_\_\_\_ Feet of \_\_\_\_\_ Inch \_\_\_\_\_ # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe  
+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Cement circulated \_\_\_\_\_ No. of Sacks \_\_\_\_\_

Cemented by \_\_\_\_\_ Witnessed by \_\_\_\_\_

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used Mix + pour Witnessed by L. Gallagher

Remarks: \_\_\_\_\_

Plugging follow

1. 10' at 510  
cut + pulled 20' of 7"  
2. 10' at 250 7-19-61