

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

June 3, 1946
Date

Artesia, New Mexico
Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

E. E. SCANNELL ET AL STATE _____ Well No. 2-A in the _____
Company or Operator Lease

NW 1/4 SE 1/4 of Sec. 30, T. 17-S, R. 28-E, N. M. P. M.,
Empire Field, _____ Eddy County.

The dates of this work were as follows: May 26 to June 2, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a Total Depth of 1800', with a gas show from 1729 to 1735'. Water was encountered from 277 to 292'. The hole was plugged from total depth to 1700' by Halliburton, a cement plug of 5 sacks of cement was set, the hole plugged with heavy mud to 800' and a plug of 20 sacks of cement was set, the hole plugged with heavy mud to 405' where a plug of 5 sacks of cement was set, the hole plugged to the surface where a cap of 5 sacks of cement and the regulation marker was set. Before pulling casing all appearances of gas had quit.

Witnessed by _____ Name E. E. Scannell et al Company _____ Geol. Engr. _____ Title _____

Subscribed and sworn before me this _____ I hereby swear or affirm that the information given above is true and correct.

_____ day of _____, 19____ Name _____

_____ Position _____

Notary Public _____ Representing _____

Company or Operator

My commission expires _____ Address _____

Remarks:

Name

Title