

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED

MAY 29 1961

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. Approval will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

May 24, 1961

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum CorporationState CCWell No. 1 in 6

(Unit)

SW NE 31 17-S 24-Y Undesignated Padlock Well out Pool
(40-acre Subdivision) 1/4 of Sec. T. R. NMPM.
Eddy County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

After running logs, setting 5-1/2" casing, and dressing plug to 5992, the shoe was perforated 5920'-47', 5882'-5908', 5870'-5875' w/2SPF. Acidized with 10,000 gallons regular acid; reacidized with 20,000 gallons NE acid. No recover of oil or gas. Set GI retainer at 5865' and cement squeezed perforations. Cut sandril slot 5852'-58' and acidized with 10,000 gallons regular acid. Reacidized with 30,000 gallons retarded acid. Lack 315 barrels of lead water to recover. We propose to abandon the shoe formation and attempt Padlock completion by cementing perforations 5852'-58' with 100 sz. also set cement. Set bridge plug at 3700', perforate Padlock 3510'-45' with 2SPF, acidize with 3,500 gallons regular acid, swab and evaluate.

Approved..... MAY 29 1961
Except as follows:....., 19.....

Approved
OIL CONSERVATION COMMISSIONBy W. A. GrissettTitle Oil and Gas Inspector

Pan American Petroleum Corporation

Original Signed by: Company or OperatorBy V. E. STALEYPosition Area Superintendent

Send Communications regarding well to:

Name V. E. StaleyAddress Box 68, Hobbs, New Mexico

OIL CONSERVATION COMMISSION		
ARTESIA DISTRICT OFFICE		
No. Copies Received	5	
DISTRIBUTION		
	NO RECEIVED	
DIRECTOR		
CHIEF OF BUREAU		
PRODUCTION OFFICE		
STATE LAND OFFICE		
U. S. G. S.		
TRANSPORTER		
FILE		
BUREAU OF MINES		