

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Otis A. Roberts

Artesia, New Mexico

Company or Operator
Parker-State
Well No. 1 in SW SE of Sec. 31, T. 17 S
Lease
R. 28 E, N. M. P. M., Artesia Field, Eddy County.
Well is 4950 feet south of the North line and 1650 feet west of the East line of Section 31
If State land the oil and gas lease is No. B-2071 Assignment No. 8
If patented land the owner is , Address
If Government land the permittee is , Address
The Lessee is Otis A. Roberts, Address Artesia, New Mexico
Drilling commenced 12-29-41 19 Drilling was completed 1-18-42 19
Name of drilling contractor Company tools, Address
Elevation above sea level at top of casing 3690 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 653 to 861 No. 4, from to
No. 2, from 683 to 695 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 330 to 340 feet. 2 bailers over night
No. 2, from 390 to 400 feet. 3 bailers over night
No. 3, from 510 to 525 feet. sulphur water 3 bailers over night
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8 1/2	32 1/2	8		441	Reg.			water string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	441				12 sacks

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 742 feet, and from feet to feet

PRODUCTION

Put to producing, 19
The production of the first 24 hours was 0 barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

C. H. Beasley, Driller
Harry Pinson, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Artesia, New Mex. 1-19-42

Place

Date

I swear to before me this 19

Name

Position Owner

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	25	25	Lime
25	55	30	Red Bed
55	165	110	Gyp & red shale
165	220	55	Anhy
220	228	8	Red Bed
228	330	102	Anhy
330	332	2	Blue Shale
332	340	8	Anhy
340	345	5	Red Bed
345	350	5	Anhy
350	360	10	Red Bed
360	390	30	Red Sand & Gravel
390	400	10	Gravel (Water)
400	426	26	Anhy
426	438	12	Red Bed
438	470	32	Anhy
470	482	12	Red Bed
482	507	25	Broken Gyp & Red Bed
507	525	18	Anhy & Lime (sulphur water 510-525)
525	535	10	Anhy
535	565	30	Broken Gyp & Anhy
565	568	3	Gyp & Brown Shale
568	580	12	Anhy & Gyp
580	585	5	Brown Lime
585	590	5	Anhy
590	597	7	Red Shale
597	630	33	Anhy
630	637	7	Gray Lime
637	646	9	Anhy
646	653	7	Gyp
653	661	8	Brown Lime (show oil)
661	672	11	Anhy & Lime Shells
672	675	3	Gray Lime
675	680	5	Broken Anhy
680	688	8	Gray Lime
688	695	7	Brown Lime (Show oil)
695	700	5	Anhy
700	706	6	Lime & Anhy
706	710	4	Gyp & Blue Shale
710	725	15	Shale & Lime
725	735	10	Lime & Anhy
735	742	7	Lime
742			Total Depth