

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION  
JAN 29 1979

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**O. C. C.**  
**ARTESIA, OFFICE**

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. E-949	
7. Unit Agreement Name	
8. Farm or Lease Name Sinclair State	
9. Well No. 1 1	
10. Field and Pool, or Wildcat Artesia Qn. Grayburg SA	
12. County Eddy	

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Yates Drilling Company	
3. Address of Operator 207 So. 4th St., Artesia, NM 88210	
4. Location of Well UNIT LETTER M, 400 FEET FROM THE West LINE AND 990 FEET FROM THE South LINE, SECTION 35 TOWNSHIP 17S RANGE 28E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Bradenhead test <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Well head was dug out to 8-5/8 surface csg. 4 1/2 csg was setting on 8-5/8 with csg clamps - 1" pipe was grouted between 4 1/2 and 8-5/8 with 3 sxs cement - 1" brought to surface - 1" valve on top. Inspected by Mr. Weaver with Oil Conservation Division.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ben Davis TITLE Drilling Supt. DATE 1/26/79

APPROVED BY B.W. Weaver TITLE OIL AND GAS INSPECTOR DATE JAN 30 1979

CONDITIONS OF APPROVAL, IF ANY: