

COPIES RECEIVED	3
TRIBUTION	
FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

DEC 12 1973

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
647	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Atlantic Richfield Company		"G"
3. Address of Operator		9. Well No.
P. O. Box 1710, Hobbs, New Mexico 88240		35
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>J</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM		Empire - Abo
THE <u>East</u> LINE, SECTION <u>34</u> TOWNSHIP <u>17S</u> RANGE <u>28E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3672' DF		Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has developed pressure & a salt water flow from the 5½" X 8-5/8" annulus. To protect the 5½" casing, we propose to perforate 4 holes about 30' above the top of cement at approx. 2925' & cement w/600 sx of Class C + 4% gel. This should circulate cement to the surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A.D. Sletcher TITLE Dist. Drlg. Supv. DATE 12/11/73

APPROVED BY W.A. Gussett TITLE OIL AND GAS INSPECTOR DATE DEC 12 1973

CONDITIONS OF APPROVAL, IF ANY:

Notify N.M.O.C.C. in sufficient time to witness

Coman