Carryle SF

Form 9-331 (May 1963)

16.

N. M. O. C. C. COPY

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

NM 068677 6. HF INDIAN, ALLOTTRE OR TRIBE NAME.

A111 1M D11	\ 1 \\ \T1 \\ \T \	A 1 1 1 1 1 1	- 1 CO CO CO CO	~~ * * * * * * * * * * * * * * * * * *	. ^
CHAILDY	NW 1111 5-X	$\Delta \Delta \Delta B$	CAN THE	1 35A 1 A75-1	
SUNDRY	131 / 111 / 13	A 1 3 1 1	10.11.10.20.1.3	CIIV VVI	1 3

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) E C E I V E D 7. UNIT AGREEMENT NAME WELL X GAS WELL FFB 5 1975 8. FARM OR LEASE NAME McCLELLAN OIL CORPORATION HINKLE FEDERAL 3. ADDRESS OF OPERATOR 9. WELL NO. , c. c. Box 848, Roswell, New Mexico ARTEBIA, OFFICE LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface 10. FIELD AND POOL, OR WILDCAT WILDCAT 11. SEC., T., R., M., OF BLK. AND SURVEY OR ARMA 660' FSL & 1980' FEL SEC. 8, 165 - 29E 12. COUNTY OR PARISH 13. STATE 15. ELEVATIONS (Show whether DF, RT. GR. etc.) 14. PERMIT NO. 3678' G. L.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING ABANDONMENT*	Х
REPAIR WELL		CHANGE PLANS		(Other)	
(Other)				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Re-entered old Hole & set wire line Bridge @ 2360' IN EXISTING 55" CSG. PERFORATED 2 SHOTS/FT 22981-23001, 2305'-2313'. RAN TUBING AND SET PACKER@ 2100'. ACIDIZED W/1000 GALS. SWABBED DRY. NO FLUID OR GAS. WELL WAS P & A AS PER VERBAL INSTRUCTIONS ISSUED 9/7/73 AS FOLLOWS: PUMPED PLUG 2240'-2340', 1200'-1300', 280'-380'. PLUG AT SURFACE. WILL RE-INSTALL MARKER AND CLEAN LOCATION.

18. I hereby centify that the foregoing is true and correct PRESIDENT (This space for Federal or State office use) ARPROLING BY CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side