

RECEIVED BY
Form 9-331
Dec. 1973

FEB 22 1985

UNITED STATES

DEPARTMENT OF THE INTERIOR

O. C. D.

GEOLOGICAL SURVEY

ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Phillips Oil Company

3. ADDRESS OF OPERATOR

Room 401, 4001 Penbrook St., Odessa, Tx 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit D, 660' FN&W lines

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC-061638

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Hi Lonesome

8. FARM OR LEASE NAME

East High Lonesome Fed

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Hi Lonesome Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 13, T-16-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

30-015-02692

15. ELEVATIONS (SHOW DF, KDB, AND WD) NR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1-23-85: 2078'PTD Pulled rods and pump. Installed BOP. Pulled tbg. ran 7" csg scraper on 2-7/8" tbg to 2035'. COOH. Ran hydrostatic bailer. CO to TD. Last test: Pumped 24 hrs, 1 BO, 4 BW, no gas.
- 1-24-85: Tested 2-7/8" tbg in hole to 5000 psi. Set pkr at 1980' Pumped 20 bbls 2% KCL water w/1 drum of Unichem 756 as pre-pad. Pumped 2500 gals of gel as pad, pumped 2500 gals of gel w/10-20 sand.
- 1-25-85: Tagged fill at 2000'. CO to 2078'. Set pkr at 1980'.
- 1-27,28.-85: Well SI 48 hrs.
- 1-29,30-85: Well down.
- 1-31-85: Pumped 24 hrs, 5.85 BO, 51 BFW, 60 BLW.
- 2-01-85: Pumped 24 hrs, no oil, 102.5 BW.
- 2-02-85: SD due to weather.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE February 15, 1985

915/367-1257 (McLemore) (This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY: TITLE DATE

FEB 21 1985