

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN.M.O.C. 1 COPY
SUBMIT IN TRIPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-061638

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME AUG 27 1981
Brewer9. WELL NO. O. C. D.
14 ARIZONA, OFFICE

10. FIELD AND POOL, OR WILDCAT

High Lonesome

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 13, T-16S, R-29E

12. COUNTY OR PARISH 18. STATE

Eddy New Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER Water Injection

2. NAME OF OPERATOR
General American Oil Company of Texas

3. ADDRESS OF OPERATOR
P. O. Box 128, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FNL & 1977' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3741' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon the above well as follows:

1. Pull tubing.
2. Spot 100' plug from 2150'-2050' to cover open hole section, 2150'-2124'.
1100' Top of YATES
3. Perforate 4 holes @ 927', Base of Salt, and squeeze 55 sacks cement into formation.
4. Perforate 4 holes @ 465', 25 ft above 490', Top of Salt, and squeeze 55 sacks cement into formation.
5. Perforate 4 holes @ 350', water zone, and squeeze 55 sacks cement into formation.
6. Set 10 sack surface plug.
7. Erect permanent well marker.

AUG 20 1981

18. I hereby certify that the foregoing is true and correct

SIGNED M. S. SanningTITLE EngineerDATE August 18, 1981

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:Changes in steps 2, 3 & 4 see attached general
requirements for procedures of step 2

*See Instructions on Reverse Side

APPROVED AS AMENDED

AUG 26 1981

O. C. D.
For JAMES A. GILLHAM
DISTRICT SUPERVISOR



United States Department of the Interior

GEOLOGICAL SURVEY
South Central Region
Roswell District
P.O. Drawer 1857
Roswell, New Mexico 88202-1857

Re: Permanent Abandonment

Well: No. 14 Brewer

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases".
2. The Artesia office (Telephone (505) 746-9838) is to be notified in sufficient time for a representative to witness all plugging operations.
3. Blowout prevention equipment is required.
4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Bureau of Land Management for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
5. Our records indicate T.D. to be @ 2637'. In Step 2, fill open hole with mud and place a minimum of 50 feet of cement across shoe of 7" csg leaving at least 50' in csg. Wait on cement and tag plug. Continue with program as approved.