

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
NM OIL & GAS IN TRIPLI  
ARTEZIA, NM 88210

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-061638

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection MAR 10 1983

2. NAME OF OPERATOR General American Oil Company of Texas O. C. D.

3. ADDRESS OF OPERATOR P. O. Box 128 Loco Hills, New Mexico 88255 ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FNL and 990' FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brewer

9. WELL NO.

25

10. FIELD AND POOL, OR WILDCAT

High Lonesome

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13, T-16S, R-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3747' DF

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

The following work was completed December 10 — 22, 1981:

1. Attempted to pull tubing. Efforts unsuccessful as tubing was falling apart and hole was scaled up @ 1695'.
2. Set cement retainer @ 1550'. Pump 20 sack cement through retainer, and leave 20 sack cement on top of retainer.
3. Load hole with mud.
4. Perforated 4 holes @ 1109' (Top of Yates) and squeezed 55 sack cement into formation. Top of plug in casing @ 984'.
5. Perforated 4 holes @ 475' (Top of Salt) and squeezed 55 sack cement into formation. Top of plug in casing 420'.
6. Perforated 4 holes @ 350' (Water zone) and squeezed 135 sack cement into formation. Top of plug in casing @ 180'.
7. Spot 10 sack surface plug.
8. Erect permanent marker.

Additional report will submitted when surface restoration is completed at end of nine (9) well program.

18. I hereby certify that the foregoing is true and correct

SIGNED M. B. Lanning

TITLE Engineer

DATE January 19, 1982

(This space for Federal or State Approval)

APPROVED W. A. GILLHAM  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 9 1982

FOR

JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

Post 1-22-82  
p. 2