GPO 9 18 507

Form 9-381a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	LAS Cruces
Lease No	61638
Unit	Brown #1

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTEN	TION TO DRILL	st	JBSEQUENT REPORT OF WATER SHUT-OFF	
1	TION TO CHANGE PLANS	1 11	IBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
1	TION TO TEST WATER SHUT-OFF	1 11	BSEQUENT REPORT OF ALTERING CASING.	
	TION TO RE-DRILL OR REPAIR WI		BSEQUENT REPORT OF RE-DRILLING OR REPAIR	
	ITION TO SHOOT OR ACIDIZE		BSEQUENT REPORT OF ABANDONMENT	
	ITION TO PULL OR ALTER CASING		JPPLEMENTARY WELL HISTORY	
	ITION TO ABANDON WELL	1 11		
		8	ubsequent Report of Acid & Prec z	
	(INDICATE ABOVE BY	CHECK MARK NATURE	OF REPORT, NOTICE, OR OTHER DATA)	
Well No	l is located 660		line and 660 ft. from E line of sec. 14	
			(Meridian)	
W114qq		(County or Subdiv	rision) (State or Territory)	
(State names of and	P ACID & FRAC: Ing point	DETAILS O	F WORK hts, and lengths of proposed casings; indicate mudding jobs, cement- portant proposed work)	
(State names of and	d expected depths to objective sar P ACID & PRAC: Loaded hole & brok 880 HO containing W/129 HO. Max. In SIP 1400. On water Rate 48.1 HPM. Lo	DETAILS On the state of the sta	F WORK	
(State names of and RECORD OF 6-27-58 RESULTS 8-28-58 8-29-58 8-30-58 8-31-58	d expected depths to objective sar ing point of ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Har. In SIP 1400. On water Rate 48.1 HPM. Lo 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2° El Sumbbed 306 HO in Sumbbed 462 HO in Sumbbed 462 HO in last. 3 hour. of the	DETAILS Onds; show sizes, weignts, and all other im the down W/12 30,000# 40/ 1j. Press. 1 sum in 12 hr and cil to r a & Haster H E tubing. 16 hrs. 24 hrs. E test.	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hbls. 20% SLT HGl & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. e. Total Inj., time 22 min.; Ave. Inj. ec. 1169 Hbls., Used 2 Fracumster 1200*s, inser 60. Job by Western Co.	•,
(State names of and RECORD Of 8-27-58 RESULTS 9-28-58 8-29-58 8-30-58 8-31-58 I understand the	d expected depths to objective sar ing point of ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Har. In SIP 1400. On water Rate 48.1 HPM. Lo 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2° El Sumbbed 306 HO in Sumbbed 462 HO in Sumbbed 462 HO in last. 3 hour. of the	DETAILS Onds; show sizes, weights, and all other im the down W/12 30,000# 40/ 1j. Press. 1 mm in 12 hr and cil to r a & Haster M E tubing. 16 hrs. 24 hrs. 24 hrs. 15 test. 16 approval in writing	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hhls. 20% SLT HG1 & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. 6. Total Inj., time 22 min.; Ave. Inj. 6c. 1169 Hhls., Used 2 Fracumster 1200*s, iner 60. Job by Western Co.	•,
(State names of and RECORD O. 8-27-58 RESULTS 8-28-58 8-29-58 8-30-58 1 understand the Company	d expected depths to objective sar ing point of ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Max. In SIP 1400. On wast Rate 48.1 HPM. Lo 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2" El Sumbbed 306 HO in Sumbbed 462 HO in last 3 hrs. of this plan of work must receive	DETAILS On the state of the sta	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hhls. 20% SLT HG1 & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. 6. Total Inj., time 22 min.; Ave. Inj. 6c. 1169 Hhls., Used 2 Fracumster 1200*s, iner 60. Job by Western Co.	•,
RECORD OF SECOND	d expected depths to objective sar ing point P ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Hex. In SIP 1400. On water Rate 48.1 HPM. La 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2° El Sumbbed 306 HO in Sumbbed 462 HO in Sumbbed 462 HO in that this plan of work must receive CENERAL AMERICAN (CENERAL AMERICAN (CEN	DETAILS Ones; show sizes, weignts, and all other im the down W/12 30,000 40/ 1j. Press. 1 20 in 12 hr and cil to r a & Haster M Etubing. 16 hrs. 24 hrs. 18 test. approval in writing	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hhls. 20% SLT HG1 & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. 6. Total Inj., time 22 min.; Ave. Inj. 6c. 1169 Hhls., Used 2 Fracumster 1200*s, iner 60. Job by Western Co.	•,
RECORD OF SECOND	d expected depths to objective asr ing point P ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Hex. Ir SIP 1400. On wace Rate 48.1 HPM. Lo 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2" Ki Sumbbed 306 HO in Sumbbed 462 HO in Sumbbed 462 HO in last 3 hrs. of this hat this plan of work must receiv	DETAILS Ones; show sizes, weignts, and all other im the down W/12 30,000 40/ 1j. Press. 1 20 in 12 hr and cil to r a & Haster M Etubing. 16 hrs. 24 hrs. 18 test. approval in writing	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hhls. 20% SLT HG1 & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. 6. Total Inj., time 22 min.; Ave. Inj. 6c. 1169 Hhls., Used 2 Fracumster 1200*s, iner 60. Job by Western Co.	•,
RECORD OF SECOND	d expected depths to objective sar ing point P ACID & FRAC: Loaded hole & brok 880 HO containing W/128 HO. Hex. In SIP 1400. On water Rate 48.1 HPM. La 2 Fracmaster 600°s OF ACID & FRAC: Ran 2044° of 2° El Sumbbed 306 HO in Sumbbed 462 HO in Sumbbed 462 HO in that this plan of work must receive CENERAL AMERICAN (CENERAL AMERICAN (CEN	DETAILS Ones; show sizes, weignts, and all other im the down W/12 30,000 40/ 1j. Press. 1 20 in 12 hr and cil to r a & Haster M Etubing. 16 hrs. 24 hrs. 18 test. approval in writing	F WORK hts, and lengths of proposed casings; indicate mudding jobs, coment- portant proposed work) Hhls. 20% SLT HG1 & 166 RO, followed by 60 & 21,000/ 20/40 Ottern Sund. Flumbed 900 paig; minimum 1800; 50 1750; 25 min. 6. Total Inj., time 22 min.; Ave. Inj. 6c. 1169 Hhls., Used 2 Fracumster 1200*s, iner 60. Job by Western Co.	••