

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-061638

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brewer

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

High Lonesome

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14, T-16S, R-29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
General American Oil Company of Texas ✓

3. ADDRESS OF OPERATOR
P. O. Box 128 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State and Federal laws.
See also space 17 below.)
At surface
1980' FNL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether of surface or bottom of hole)
ARTESIA, NEW MEXICO

DEC 18 1980

DEC 11 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Re-cement

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work was done:

1. Dug small workover pit.
2. Set 7" cast iron bridge plug @ 2,000', loaded hole with water and ran Acoustilog (Top of cement outside casing 1600').
3. Dumped 45' cement on top of bridge plug.
4. Shot 4 holes @ 1577' and cemented casing (Top of cement outside casing 710').
5. Perforated: 1370' - 1385' 2 shots per foot.
6. Sand frac above zone with 15,000 gallons gelled water containing 15,000# of 20/40 mesh bulk sand.
7. Return well to production.

18. I hereby certify that the foregoing is true and correct

SIGNED Rendell M. HawkinsTITLE Field SuperintendentDATE December 10, 1980

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD
DATE

DEC 15 1980

U.S. GEOLOGICAL SURVEY
DOWNEY, ARIZONA

*See Instructions on Reverse Side