

C/S H

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ water injection
2. NAME OF OPERATOR
General American Oil Company of Texas
3. ADDRESS OF OPERATOR
P.O. Box 128 Loco Hills, N. M. 88255
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL and 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	

5. LEASE
LC-061638
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME RECEIVED
8. FARM OR LEASE NAME Brewer MAR 10 1983
9. WELL NO. #5 O. C. D.
10. FIELD OR WILDCAT NAME ARTESIA, OFFICE High Lonesome
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14, T-16S, R-29E
12. COUNTY OR PARISH Eddy 13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3729' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned as follows:

1. 100' plug was set from 2078'-1978' to cover open hole section, 2078'-2052'.
2. Perforated 4 holes @ 1060', top of Yates, and squeezed 55 sack of cement into formation.
3. Perforated 4 holes @ 425', 25' above top of salt, and squeezed 55 sacks of into formation.
4. Perforated 4 holes @ 350', water zone, and squeezed 55 sacks of cement into formation.
5. 10 sack plug was set at the surface.
6. Permanent well marker was erected.
7. Location and road was cleaned, ripped and re-seeded.

Subsurface Safety Valve: Manu. and Type

OIL & GAS
MINERALS & MINT. SERVICE
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct Field

SIGNED Randall T. Hawkins TITLE Superintendent DATE August 26, 1982

APPROVED (This space for Federal or State office use)

APPROVED BY James A. Gillham TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 9 1983

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

Posted 10-2
9-17-82
p a