


(SUBMIT IN TRIPLICATE)

Land Office New MexicoLease No. 04711

Unit \_\_\_\_\_

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY30-015-02723

## SUNDRY NOTICES AND REPORTS ON WELLS

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 9, 1956

Federal "H" Lease

Well No. 1-15 is located 660 ft. from N line and 660 ft. from W line of sec. 15SW 1/4 Sec. 15  
(1/4 Sec. and Sec. No.)16-S 29-S  
(Twp.) (Range)N.M.P.M.  
(Meridian)High Lonesome  
(Field)Edgy  
(County or Subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I propose to drill this well with cable tools to a total depth of 1935'. Surface casing for the well, 8-5/8", will be run to a depth of 410' and cemented with 50 sacks.

The oil string, <sup>5 1/2"</sup> to be set in the anhydrite caprock, will be run to a depth of 1900' and cemented with 75 sacks.

All casing run and cemented will conform with the regulations set out by the Geological Survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John H. TriggAddress P. C. Box 5629Roswell, New MexicoBy John H. Trigg  
Title Owner