


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_  
Lease No. 100257  
Unit \_\_\_\_\_



30-015-02227

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 17, 1955

Well No. Davis 13 located 660 ft. from [N] line and 660 ft. from [E] line of sec. 15  
NW/4 NW/4 15 165 39E \_\_\_\_\_  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Unincorporated 1347 New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3679 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 12 1/4" hole to 400' with air and water, run approx. 400' of new 8 5/8" J-55 24' casing, cementing with 150 sacks cement.  
 Drill 7 7/8" hole with air and mud to approx. 1900'. Run approx. 1900' new 5 1/2" J-55 14' casing cementing with 100 sacks cement.  
 Drill the pay section with air, run 2" API tubing and sand frac.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Moab Drilling Company

Address P.O. Box 284

Artesia, New Mexico

By Robert F. Evans

Title Geologist