



County Eddy Depth 2000' Pool Undesignated* (High Lonesome)

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Moab Drilg. Co. Well No. 1 Lease State

1980' Feet from N. Line 660' Feet from W. Line, Sec. 16 Twp. 16S Rge. 29E

Spl.

Land State Contractor Company Rig

Elevation 3662' Spudded 1-31-55 Completed 3-13-55

T. A
T. X 402
B. X 650'
T. Del Li
T. Del Sd
T. Y 810
T. SR
T. Q 1548' 1560
T. PR
T. GB
T. SA
T. Glo
T. Blby
T. CF

T. Tu Total Depth 1810' P.B.
T. Full Top Pay 1750 District 6
T. DR I.P.P 48 BOPD
T. Wich A. Base on 12 BO 6 Hrs.
T. Abo Choke: open Inch
T. WC Tubing 2 @ 1800 Ft.
T. Hu Press: Tbg. Csg.
T. Per-Pe GOR Gravity 23.1
T. Penn Effective Perfs.:
T. Strawn
T. Miss
T. WF

Acid, Frac & Shooting Record:

T. Dev
T. Sil Solrac From To
T. Fuss 16,000 g From OH 1750 To 1810
T. Mon From To
T. Simp From To
T. McK
T. Ell
T. G.W.

SHOWS

T. Gr
T. S/
T. S/
T. S/
T. S/
T. S/
T. S/

CSG. & CEMENTING RECORD

Size	Feet	Sax Cement
<u>9 7/8</u>	<u>200</u>	<u>100'</u>
<u>7</u>	<u>420</u>	<u>15'</u>
<u>5 1/2</u>	<u>1750</u>	<u>50</u>

Feb. 2, 1955

Drilg. 130' R.B.

TD 280 R.B. lost Circ.

TD 420' salt, stop

TD 1582' sd sdv.

C 800-1' rw 10'

only at + sd NS

C 817-37 rw 15'

only at + sd NS

C 837-57 rw 15' sh

only + sd NS

C 1540-60 rw 17 1/2'

only + sd NS

C 1564-80 rw 16' sh

+ only NS

TD 1750' sd prep drill

TD 1809' sd prep
Cement 5 1/2

c 1770-74 new 15" sd

SLM 1774=1810 Ram $\approx 1/2$ to TD

TD 1810 sd, sucking load oil.

slf 10,000 g 1750-1810

TL 1810 sd, telg on pumps.

pu 48BO 24'