

R 29 E

[illegible]

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 840 ACRES
LOCATE WELL CORRECTLY

Moab Drilling Company

Skelly - State

(Company or Operator)

(Leave)

Well No. 4, in NE $\frac{1}{4}$ of NW $\frac{1}{4}$, of Sec. 16, T. 16S, R. 29E, NMPM.

High Lonesome

Pool.

Eddy

County.

Well is 660 feet from North line and 1980 feet from West line

of Section 26 If State Land the Oil and Gas Lease No. is E-134

Drilling Commenced July 7, 1955 Drilling was Completed July 17, 1955

Name of Drilling Contractor Company Rig

Address P.O. Box 387 Moab, Utah

Elevation above sea level at Top of Tubing Head.....**3674**..... The information given is to be kept confidential until
..... 19.....

OIL SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from to No. 5, from to

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from _____ to _____ feet.

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

CASING RECORD

| SIZE | WEIGHT PER FOOT | NEW OR USED | AMOUNT | KIND OF SHOE | CUT AND PULLED FROM | PERFORATIONS | PURPOSE |
|-------|--------------------|----------------|--------|-----------------|------------------------|--------------|------------|
| 8 5/8 | 26 | used | 340 | Tex. Pat. | | | Surface |
| 5 1/2 | 15.5 | new | 1782 | Guide | | | Production |
| | | | | | | | |

MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
| 12 1/4 | 8 5/8 | 340 | 150 | pumped | | |
| 7 7/8 | 5 1/2 | 1782 | 100 | pumped | | |
| | | | | | | |

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Dry, plugged and abandoned

Result of Production Stimulation.....

Depth Cleaned Out.....

RD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1890 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

| Southeastern New Mexico | | | Northwestern New Mexico | | |
|-------------------------|------|--|-------------------------|--|-----------------------|
| T. Anhy. | | | T. Devonian | | T. Ojo Alamo |
| T. Salt | | | T. Silurian | | T. Kirtland-Fruitland |
| B. Salt | | | T. Montoya | | T. Farmington |
| T. Yates | 848 | | T. Simpson | | T. Pictured Cliffs |
| T. 7 Rivers | | | T. McKee | | T. Menefee |
| T. Queen | 1574 | | T. Ellenburger | | T. Point Lookout |
| T. Grayburg | | | T. Gr. Wash. | | T. Mancos |
| T. San Andres | | | T. Granite | | T. Dakota |
| T. Glorieta | | | T. | | T. Morrison |
| T. Drinkard | | | T. | | T. Penn. |
| T. Tubbs | | | T. | | T. |
| T. Abo | | | T. | | T. |
| T. Penn. | | | T. | | T. |
| T. Miss. | | | T. | | T. |

FORMATION RECORD

| From | To | Thickness in Feet | Formation | From | To | Thickness in Feet | Formation |
|------|------|----------------------|----------------------------------|------|----|----------------------|-----------|
| 0 | 305 | 305 | Sand, gravel, shale | | | | |
| 305 | 352 | 47 | Anhydrite, shale | | | | |
| 352 | 645 | 293 | Salt, anhydrite, shale | | | | |
| 645 | 848 | 203 | Anhydrite, shale, salt | | | | |
| 848 | 1574 | 726 | Sand, shale, lime. salt | | | | |
| 1574 | 1890 | 316 | Red sand, shale, salt, anhydrite | | | | |

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 13, 1955 (Date)
Company or Operator Moab Drilling Company Address Box 826 Artesia, New Mexico
Name Robert F. Evans Position or Title Geologist