

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1484.

5. LEASE DESIGNATION AND SERIAL NO.

NM-57524

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Big Mac Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

High Lonesome - Dresser

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 19-T16S-R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

SEP 11 1985

O. C. D.

ARTESIA, OFFICE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

3300' FEL & 660' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3597' G.L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

Cement and Logs

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

8/20/85: Rigged up Cable Tool. Pulled dry hole marker.

8/21/85: Cleaned out hole to 2100' with 8" and 6-1/4" bit.

8/22/85: Logged well using CNL-CDL-Gammaray - Dresser Atlas. Ran 45 joints  
of 4-1/2", 10.5# casing to a total depth of 1871.44'. Cemented  
with Halliburton using 135 sx Halliburton Lite and 65 sx Class "C"  
50/50 poz, 2% CaCl. Plug down at 5:30 p.m. Plug back TD - 1829'.  
No further reports till completion.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Paul R. Hagdale*

TITLE Operations Manager

DATE September 4, 1985

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

SEP 9 1985

\*See Instructions on Reverse Side