

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-0916

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Simmons Federal

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

Henshaw-Grayburg West

11. SEC., T., R., M., OR BLK. AND SURVEY OR ADMA

Sec. 23-T16S-R29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER Plug & Abandon  
2. NAME OF OPERATOR McClellan Oil Corporation 505-622-3200  
3. ADDRESS OF OPERATOR P.O. Drawer 730 Roswell, NM 88202-0730  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface  
2310' FNL & 1980' FNL

AUG 23 1991

O. C. D.  
ARTESIA. OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3723' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other) P & A

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4½ csg - 2634'

CIBP at 2550 w/35' cmt on top

2 3.8 EUE tbg

Perfs. 2504'-2509'

TOC 2000'

Top of Salt

Bottom of Salt

1. Set CIBP at 2400' & put 35' cmt on top.

2. Run tbg to 2300' & load csg w/10# gal heavy Gel H<sub>2</sub>O.

3. Shoot off csg at 2000' & pull out of hole.

4. 1st plug 2050' to 1950' 30 sxs [TAG]

2nd plug 1110' to 900' 35 sxs

3rd plug 480' to 380' 35 sxs [TAG]

4th plug 60' to Surface 20sxs

Clean location & install dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drlg. & Comp. Engineer

DATE 5-23-91

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 8/19/91

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side