

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

DEDORT ON REGINATING	-	REPORT ON RESU	ILT OF TEST	REPORT ON		
EPORT ON BEGINNING RILLING OPERATIONS		OF CASING SHUT		REPAIRING		
PORT ON RESULT	X	REPORT ON RECO	MPLETION	REPORT ON (Other)		
5-2				Tucso	n, Arizona	••••
Following is a report on the	work done	and the results obtained	under the heading	noted above at the		
Geror Oil Corporation				Gulf-State		
. A. Thomas Drillin	or Operator) ng Co.		, Well No		NE 1/4 of Sec.	32
16S R 29E NMPM.	tractor)					
•		5-2-56	,			
ne Dates of this work were as folo				52		5.6
tice of intention to do the work	(₩ā s) (was	not) submitted on Form	C-102 on	(Cross out incorrect w	nrds)	, 19
D: Plugged well as follow	ETAILED A	not obtained. (verbaccount of work tal depth 3097 fe	pone and resu	ULTS OBTAINED Sacks cement		
Plugged well as follow 0 3020 feet. Used wo or bridge. Pulled 7 degulation marker se	ws: Totald frou	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri	eet. Used 15: 00 feet. Use	ults obtained sacks cement ed 5 sacks cer eet with 5 sack	ment at 1800 ks cement.	feet
Plugged well as follow 0 3020 feet. Used wo or bridge. Pulled 7 0 segulation marker se	ws: Totald frou	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri	eet. Used 15: 00 feet. Use	ults obtained sacks cement ed 5 sacks cer eet with 5 sack	ment at 1800 ks cement.	feet
Plugged well as follow o 3020 feet. Used wo or bridge. Pulled 7 degulation marker se	ws: Totald frou	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri	eet. Used 15: 00 feet. Use	ults obtained sacks cement ed 5 sacks cer eet with 5 sack	ment at 1800 ks cement.	feet
Plugged well as follow o 3020 feet. Used wo or bridge. Pulled 7 degulation marker se	ws: Totald frou	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri	eet. Used 15: 00 feet. Use	ults obtained sacks cement ed 5 sacks cer eet with 5 sack	ment at 1800 ks cement.	feet
Plugged well as follows 3020 feet. Used wor bridge. Pulled 7 legulation marker senspection.	ws: Totaud from inch ca	account of work tal depth 3097 fer a 3020 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15: 00 feet. Used dge at 200 feetment. Pits	sacks cemented 5 sacks center with 5 sacks and location (ment at 1800 ks cement.	feet
Plugged well as follows 3020 feet. Used well as follows or bridge. Pulled 7 segulation marker semble the segulation.	ws: Totaud from inch can top	account of work tal depth 3097 fer a 3020 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15 : 00 feet. Used dge at 200 feet. Pits	sacks cemented 5 sacks center with 5 sacks and location (ment at 1800 ks cement.	feet
Plugged well as follows 3020 feet. Used well as follows or bridge. Pulled 7 segulation marker semble the segulation.	ws: Totaud from inch ca	account of work tal depth 3097 fer a 3020 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15 : 00 feet. Used 15 : dge at 200 feet. Pits omas Drilling	sacks cement ed 5 sacks cen et with 5 sach and location of	President	feet r
Plugged well as follows 3020 feet. Used to be bridge. Pulled 7 segulation marker senspection.	ws: Total desired from the state top	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15 : 00 feet. Used 15 : dge at 200 feet. Pits omas Drilling	sacks cement ed 5 sacks cen et with 5 sack and location	President	feet r
Plugged well as follows 3020 feet. Used was pridge. Pulled 7 segulation marker senspection. Witnessed by R. A. Thomproved: OIL CONSERVAT	ws: Total desired from the state top	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15: 00 feet. Used dge at 200 feetment. Pits Discourage Drilling (Company) I hereby certify the to the best of my	sacks cement ed 5 sacks cement ed 5 sacks cement ed 5 sacks cement et with 5 sacks and location of the the information of knowledge.	President	feet r
Plugged well as follows 3020 feet. Used was pridge. Pulled 7 segulation marker senspection. Witnessed by R. A. Thomproved: OIL CONSERVAT	ws: Total from inch can take to at top	ACCOUNT OF WORK tal depth 3097 feet to 18 sing and set bri with 5 sacks ce	eet. Used 15: 00 feet. Use dge at 200 feetement. Pits Omas Drilling (Company) I hereby certify to the best of my Name Position	sacks cement ed 5 sacks cen et with 5 sack and location	President (Title)	feet r