

Form 5-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN APPLICATION
(Other Instructions on Reverse Side)Form approved
Bureau of Reclamation No. 41-11111

5. TRADE DESIGNATION AND SERIAL NO.

LC-037777 (6)

6. IF DESIGN, TRADE, OR SERIAL NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ *Water Injection Well*2. NAME OF OPERATOR
Continental Oil Company3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, New Mexico 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL + 1980' FEL of Sec. 34

7. UNIT AGREEMENT NAME

Forest Pool

8. FARM OR LEASE NAME

Forest Pool unit

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Source Lake G-5A

11. COUNTY, T., R., S., OR 10-MIN. AND
SURVEY OR AREA

Sec. 34, T-16S, R-29E

RECEIVED

RECEIVED

JUN 18 1970

12. PERMIT NO.

15. EXPLANATIONS (Show whether DE, RE, OR, etc.)

3663' DF

U.S. GEOLOGICAL SURVEY

12. COUNTY OR PARISH

Socorro

13. STATE

N.M.

JUN 19 1970

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

O. C. C.
ARTESIAN OFFICE

NOTICE OF INTENTION TO:

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Resumption Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and bottom hole
next to this work.)

This well was cleaned out to 2737'. Per 4
set 3 1/2" 9.3# casing. Cemented with 100 sacks
around casing shoe. Per 1 1/4" tubing and set
another 100 sack at surface. Temperature
survey indicates cement from TD to 2400' and
from 1000' to 100'. WOC 24 hrs.
Finished filling hole with 5 yards of "ready
mix" cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Section Chief

DATE 6-16-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

DATE

USGS-5

CRA

JUN 18 1970

ACCEPTED FOR RECORD PURPOSES
ACTING District Engineer

*See Instructions on Reverse Side