

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY N. M. O. C. C. COPYSUBMIT IN TRIF
(Other instructio.
verse side)Copy to SF
Form approved
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	WATER INJECTED RECEIVED	7. UNIT AGREEMENT NAME FOREST POOL
2. NAME OF OPERATOR CONTINENTAL OIL COMPANY	APR 14 1976	8. NAME OR LEASE NAME FOREST POOL UNIT
3. ADDRESS OF OPERATOR Box 460, HOBBS, N.M. 88240		9. WELL NO. 7
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FNL & 990' FEL OF SEC. 34	ARTESIA. OFFICE	10. FIELD AND POOL, OR WILDCAT SQUARE LAKE G-SH
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3670' DF (Est.)	11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA SEC. 34, T-16S, R-29E
		12. COUNTY OR PARISH EDDY
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

There are no remaining commercial reserves on this lease. All wells will be plugged; the above named well by the following procedure:

Remove tubing. Run tubing w/cement retainer to set @ 1800'. Squeeze open hole w/225 sks. Class "C" cmt. Will not reverse out any excess. Pull out retainer & spot 25-50 sks. cmt above retainer.

Pull tubing to 500' & spot 100 sks plug to stc.

ERECT Dry Hole marker.

(No casing will be removed).

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APR 15 1976

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
DEC 12 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICOArtesia
11525-5 Partner. File