

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1491.
5. LEASE DESIGNATION AND SERIAL NO.
LC - 037777 6
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Continental Oil Company		8. FARM OR LEASE NAME EVERS 8	
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, New Mexico 88240		9. SERIAL NO. 8	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL + 660' FEL of Sec. 34, T-16S, R-29E, in EDDY COUNTY, N. MEX.		10. FIELD AND POOL, OR WILDCAT FOREST POOL	
11. PERMIT NO.		12. COUNTY OR PARISH EDDY	
15. ELEVATIONS (Show whether DF, ET, GR, etc.) 3645' DF		13. STATE N. MEX.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	FULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☒	(Other) ☐	(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to convert this well to water injection by the following procedures.

Side-track hole above junk at 2626' and drill to approx. 2685'. Run 3 1/2" OD tubing to TD + cement with 80 sacks of class C cement. Reciprocate tubing for 30 minutes prior to cementing and while cementing. Run GR/N log and perforate. Treat pipe with treated water and 200 gals. 15% LSTHE. Place well on injection. Work to commence as soon as approved.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Section Chief

DATE

12-11-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

USGS-5

FIDEI 2 196

R. L. BECKMA

*See Instructions on Reverse Side

DEC 15 1969

O. C. C.
ARTESIA, OFFICE