

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-037777(6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ *Water Injection*

2. NAME OF OPERATOR *Continental oil Co.*

3. ADDRESS OF OPERATOR *Box 460 Hobbs, N.M.*

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface *660' FSL and 660' FEL of Sec 34*

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.) *ARTESIA, OFFICE*

7. UNIT AGREEMENT NAME

Forest Pool

8. FARM OR LEASE NAME

Forest Pool Unit

9. WELL NO.

19

10. FIELD AND POOL, OR WILDCAT

*Square Lake G-SA*11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA*Sec 34 T-16S R-29E*

12. COUNTY OR PARISH

Eddy N Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) *Shut-off water*PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐(Other) *X*

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to shut off water by the following procedures: Plug back in open hole to 2490' w/ pea gravel and/or sand. Set cement retainer at $\pm$ 2400' and squeeze open hole 2477'-2490' w/ 100 sacks Class C cement. Drill out plug and pressure test to 700 psi.

RECEIVED

JAN 12 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED *Robert Paul*TITLE *Admin Supervisor*DATE *1-11-73*

(This space for Federal or State office use)

TITLE

DATE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

JAN 12 1973

H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side