

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-037777(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection JAN 15 1973

2. NAME OF OPERATOR Continental Oil Co.

3. ADDRESS OF OPERATOR Box 460 Hobbs, New Mexico D.C.C. ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL and 660' FWL of Sec 35

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME

Forest Pool

8. FARM OR LEASE NAME

Forest Pool Unit

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Square Lake G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 35, T-16S, R-29E

12. COUNTY OR PARISH 13. STATE

Eddy, N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐Selective plug ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to selectively plug this well by the following procedures: Plug back in open hole to base Youngton sand (est 2640') using Class C cement. Set cement-lined tubing at $\pm 2488'$ and place back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault III

TITLE

Admin Supervisor

DATE

1-11-73

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APPROVED
JAN 12 1973
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

N. M. O. C. C. - 5 CRA-1 File