

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Marbob Energy Corporation

3. Address and Telephone No.

P.O. Drawer 217 Artesia, NM. 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

651' FWL & 517' FWL
Sec. 35 T-16-S R-29-E

5. Lease Designation and Serial No.

LC-037777 "B"

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Forest Pool Unit

8. Well Name and No.

2

9. API Well No.

30-015-02808

10. Field and Pool, or Exploratory Area

Square Lake GSA

11. County or Parish, State

Eddy N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Start work on 4/20/94 Complete work on 4/21/94

- (1) Set 5½ CIBP @ 2400', cap w/14 sacks cement
- (2) Load hole w/mud
- (3) Perforate 5½ casing @ 900' and circulate cement to surface w/255 sacks, W.O.C. Cement fell to 78' from surface, filled 5½ casing from 78' to surface & from 78' to surface between 5½ casing and 8 5/8 casing w/30 sacks cement, set P&A marker

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Raymond M. Malherbe

Title Supervisor

Date 5-6-94

(This space for Federal or State office use)

Approved by (ORIG. SGD.) JOE G. LARA

Title PETROLEUM ENGINEER

Date 5/26/94