

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)DATE
to reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	JAN 15 1973	7. UNIT AGREEMENT NAME Forest Pool
2. NAME OF OPERATOR Continental Oil Co.		8. FARM OR LEASE NAME Forest Pool Unit
3. ADDRESS OF OPERATOR BOX 460 Hobbs, N. M.	O. E. G. AREA OFFICE	9. WELL NO. 9
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL and 330' FWL of Sec 35		10. FIELD AND POOL, OR WILDCAT Square Lake G-5A
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 35 T-16S R-29E
		12. COUNTY OR PARISH Cady
		13. STATE N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to squeeze the Premier perms to isolate the Lovington Sand in the open hole completion by the following procedures: Plug back in open hole w/ pea gravel and sand to 2580'-2570'. Squeeze perms 2532'-2558' w/ 100 sacks class C Cement. Drill out plug to 2560'-2565' and pressure test squeeze to 700 psi.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault

TITLE

Admin. Supervisor

DATE

1-11-73

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 12 1973
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS-Antesia-5 CRA-1 File