

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED BY

SEP 29 1986

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR

Mobil Producing TX. & N.M. Inc. O. C. D.

3. ADDRESS OF OPERATOR Nine Greenways Plaza, Suite 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL & 1650' FWL, Sec. 3, T16S, R30E

AT TOP PROD. INTERVAL: Same as surface

AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

LC-069465

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

W. Henshaw Premier Unit, Tr. 5

8. FARM OR LEASE NAME

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

West Henshaw Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T-16S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3855' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 07/23/84 WIH w/2-3/8 tbg to 2785', circ hole w/9.5# mud laden fluid, set cmt ret @ 2785', cmt sqz below ret into Premier perfs 2864-2916 w/25x cmt, cap ret w/ 55x cmt, POH w/stinger, perf 4 holes @ 1320', WIH w/ pkr to 900, cmt sqz 37x Class C cmt into sqz holes @ 1320.
- 07/24/84 Ran sinker bar & tag TOC @ 1234', POH w/pkr, perf 4 holes @ 400', WIH w/pkr to 250, cmt sqz perfs @ 400' w/25x Class C cmt, POH w/pkr, tag TOC @ 300, cut off wellhead, spot 5x Class C cmt from 20' to surface, rel Mayo Marrs Csg Pullers.
- 07/27/84 Weld on P&A marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paula D. Collins TITLE Authorized Agent DATE 08/02/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9-23-84
CONDITIONS OF APPROVAL, IF ANY: