

45F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

SEP 29 '88

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR

Mobil Producing TX. & N.M. Inc. ✓

3. ADDRESS OF OPERATOR Nine Greenway Plaza,
Suite 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2334' FNL & 330' FEL, Sec. 3, T16S, R30E

AT TOP PROD. INTERVAL: same as surface

AT TOTAL DEPTH: same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

O/C.D.
ARTESIA, OFFICE

5. LEASE

NM 01171A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Henshaw Premier Unit Tr. 7C

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

West Henshaw Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T-16S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3890 DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07/10/84 MIRU Mayo Marrs Csg Pullers.

07/11/84 RIH w/ 5-1/2" cmt ret, set ret @ 2800, displ hole w/70 bbls 9.5# mud, stung into ret, sqzd Premier perfs 2830-2840 & OHZ 2858-2773 w/25x Class C neat cmt, pulled out of ret, spot 5x cmt on top of ret @ 2800, TOC @ 2750.

07/12/84 Perfed 5-1/2" csg w/4 shots @ 1250', RIH w/pkr to 1000, sqzd perfs w/40x Class C cmt, displ cmt to 1150, WOC 3 hrs, tagged TOC @ 1150, POH w/pkr Perf 5-1/2" csg @ 425, RIH w/pkr to 200, sqzd perfs @ 425 w/45x Class C cmt, displ cmt to 250.

07/13/84 RIH w/tbg to 60', spot 5x Class C cmt 60' to surface, POH w/tbg, placed P&A marker, rel Mayo Marrs @ 1 PM, notified BLM, job not witnessed.

Post FD-2
10-14-88
PFA

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paula W. Collins TITLE Authorized Agent DATE 07/24/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9-25-88
CONDITIONS OF APPROVAL, IF ANY:

Approved by _____
Liability under _____
surface _____

*See Instructions on Reverse Side