

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other P X A ☒2. NAME OF OPERATOR
Amoco Production Company3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FEL
AT TOP PROD. INTERVAL: (Unit W)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC-067610

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Bosworth Federal

JAN 30 1981

9. WELL NO.

1

O.C.D.

10. FIELD OR WILDCAT NAME

West Henshaw Grayburg

ARTESIA, OFFICE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

4-16-30

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
RDB 3839'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well per the following:

Bleed off surface pressure and flow well until it dies. Pull 2-3/8" tubing. Set a cement retainer at 2800'. Squeeze perforations 2815'-30' and 2840'-53' with 50 SX Class C cement. Perforate 5-1/2" casing at * 561' with 4 jet shots. Set a retainer at 511' and circulate 100 SX Class C cement up 5-1/2" annulus. Set a ~~20~~ Class C cement surface plug. Weld on cap and erect P X A marker. *

0+4-USGS, A

HOWARD L. SUSP

LBG

1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and

OIL CONSERVATION DIVISION

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Denton Green

TITLE

Ast. Adm. Analyst

DATE

1-20-81

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) PETER W. CHESTER

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 23 1981

CONDITIONS OF APPROVAL, IF ANY:

* Perforate 1253' cement 1253' to 1053'
" 663' " 663' to 463'
15 SX surface plug.

*See Instructions on Reverse Side