

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

A blank sheet of graph paper with a grid pattern. The grid consists of 10 columns and 8 rows of squares, formed by thin black lines. The entire grid is enclosed within a thicker black border. There are no markings or text on the page.

LOCATE WELL CORRECTLY

The summary on this page is for the condition of the well at above date.

Commenced drilling _____, 1934 _____
Finished drilling _____, 1934 _____

(D) 4d con store(D)

Shell Spencer-Federal A-1, spudded 6-28-57, drilled 11" hole to 520', cemented 536' casing & 500' A/500 ex. drilled 7 7/8" hole to 2755'. Cored 7 3/4" hole to 2671'. ran det 2768' - 2671' which showed gas at rate of 1000 mcf/d. casing was cemented 4 3/4" A/1000 ex. cement. 4 3/4" string 1165' set. 5 1/2" casing was cemented 2691' A/1000 ex. cement. 5 1/2" casing was cemented 2691' A/1000 ex. cement, and the well was tested 28 5/8" hole at 2768' A/28 5/8" hole. The well was shut in 2-20-57 pending further investigative data.

Serial Number	Location	Depth of well	Kind of material used	Position	Results of pumping or bailing
1	...	...	...	...	...
2	...	...	...	...	...
3	...	...	...	...	...
4	...	...	...	...	...
5	...	...	...	...	...
6	...	...	...	...	...
7	...	...	...	...	...
8	...	...	...	...	...
9	...	...	...	...	...
10	...	...	...	...	...

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

[illegible]