orm 9-331a (Feb. 1951)			
	(SUBMI	T IN TRIPLICATE)	Land Offic 060398
	Uni	TED STATES	Lease No.
		T OF THE INTER	lor Unit
		OGICAL SURVEY	
SI	UNDRY NOTICES A	AND REPORT	S ON WELLS
r	· · · · · · · · · · · · · · · · · · ·		
	ON TO DRILL		OF WATER SHUT-OFF
1	ON TO TEST WATER SHUT-OFF		OF ALTERING CASING
	ON TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT	OF RE-DIVILLING OR REPAIR
NOTICE OF INTENTION	ON TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT	OF ABANDONMENT
1	ON TO PULL OR ALTER CASING		L HISTORY
NOTICE OF INTENTI	ION TO ABANDON WELL		
	(INDICATE ABOVE BY CHECK MAR	K NATURE OF REPORT, NOTICE	, OR OTHER DATA)
			March 25, 1957
6	Padama 1		V 4 4
Spencer	660	XXX	
Well No. 🤳	is located ft. from	$\mathbf{m} \{ \mathbf{S} \}$ line and	ft. from $\begin{bmatrix} \mathbf{L} \\ \mathbf{W} \end{bmatrix}$ line of sec.
SW SW S	ec 4 16 S	30 B M	PX
(1/ Sec. and E	Sec. No.) (Twp.)		feridian)
sest Hensi	haw (ext. : Bacy		(State or Territory)
(Field	i) (Count	y or Subdivision)	(state or removy)
The elevation o	of the derrick floor above sea l	evel is ft.	ett de l'ainlaar ter
A ALC OICTUCION O			
		AILS OF WORK	proposed casings, indicate mudding job
(State names of and e	expected depths to objective sands; show a	lizes, weights, and lengths of	proposed casings; indicate mudding jobs ork)
·	expected depths to objective sands; show ing points, and al	sizes, weights, and lengths of l other important proposed w	ly 500 of new 8 5
Proposed t	expected depths to objective sands; show ing points, and al	izes, weights, and lengths of l other important proposed w Approxime (aly 100° of new 8 5 and commented with 7
Proposed to API J-55	expected depths to objective sands; show ing points, and al embative (lepth 3000)	izes, weights, and lengths of l other important proposed w Approximet will be run 100° of new 7	aly 500° of new 8 5 and comented with 7 " 0.1. grade "H" 17
Proposed to API J-55 sacks come	expected depths to objective sands; show ing points, and al entative (lepth 3000) 28/ seemless cating at. Approximately	izes, weights, and lengths of lother important proposed w . Approximate will be run 100° of new 7	aly 500° of new 8 5 and comented with 7 " 0.1. grade "H" 17 off in the fied Sand
Proposed to API J-55 sacks coust seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the fiel Sand casing will be run ka coment. Also, w
Proposed to API J-55 sacks coust seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the fiel Sand casing will be run ka coment. Also, w
Proposed to API J-55 sacks coust seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless camin at. Approximately asing will be run for	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the fiel Sand casing will be run ka coment. Also, w
Proposed to API J-55 sacks coust seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w comenting the 52" of
Proposed to API J-55 sacks coust seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w comenting the 52" of
Proposed to API J-55 sacks come seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the fiel Sand casing will be run ka coment. Also, w
Proposed to API J-55 sacks come seamless c Approximate	expected depths to objective sands; show ing points, and al estative depth 3000 28 seamless caming at. Approximately a sing will be run fo ely 2800' of new 58	Approximate will be run will be run 100° of new 7 br water shut 200° as an 100°	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w comenting the 52" of
Proposed to API J-55 sacks course seamless c Approximato production wish to re	expected depths to objective sands; show ing points, and al embative depth 3000 28 seemless caming at. Approximately asing will be run for ely 2800' of new 52' string and comented cover the 7" water to	Approximate will be run will be run 100° of new 7 br water shut API seamless with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Froposed to AFI J-55 seeks could seasless could seasless could production wish to re	expected depths to objective sands; show ing points, and al embative depth 3000 28 seemless casing at. Approximately asing will be run for ely 2800° of new 52° string all cemented cover the 7° water of the string all cemented	izes, weights, and lengths of lother important proposed w Approximate will be run a 100° of new 7 br water shut API meanless i with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Froposed to AFI J-55 secks come seasless c Approximato production wish to re	expected depths to objective sands; show ing points, and al embative depth 3000 28 seemless casing at. Approximately asing will be run for ely 2800' of new 52' string and comented cover the 7" water of this plan of work must receive approval sectorn Ventures, In	izes, weights, and lengths of lother important proposed w Approximate will be run a 100° of new 7 br water shut API meanless i with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Foposed to AFI J-55 secks const seamless c Approximation wish to re lunderstand tha Company	expected depths to objective sands; show ing points, and al embative depth 3000 28 seemless casing at. Approximately asing will be run for ely 2800' of new 52' string and comented cover the 7" water i string and comented cover the 7" water i string fill be run for enter i string fill comented cover the 7" water i	izes, weights, and lengths of lother important proposed w Approximate will be run a 100° of new 7 br water shut API meanless i with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Froposed to AFI J-55 secks come seasless c Approximato production wish to re	expected depths to objective sands; show ing points, and al emaative depth 3000 28, seemless caming at. Approximately asing will be run for ely 2800' of new 52 string and comented cover the 7" water to the stern Ventures, In P. O. Box 445	izes, weights, and lengths of lother important proposed w Approximate will be run 100° of new 7 br water shut API seamless with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Fromosed to AFI J-55 sacks const seamless c Approximation wish to re lunderstand tha Company	expected depths to objective sands; show ing points, and al embative depth 3000 28 seemless casing at. Approximately asing will be run for ely 2800' of new 52' string and comented cover the 7" water i string and comented cover the 7" water i string fill be run for enter i string fill comented cover the 7" water i	izes, weights, and lengths of lother important proposed w Approximate will be run 100° of new 7 br water shut API seamless with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of
Foposed to AFI J-55 secks const seamless c Approximation wish to re lunderstand tha Company	expected depths to objective sands; show ing points, and al emaative depth 3000 28, seemless caming at. Approximately asing will be run for ely 2800' of new 52 string and comented cover the 7" water to the stern Ventures, In P. O. Box 445	izes, weights, and lengths of lother important proposed w Approximate will be run 100° of new 7 br water shut API seamless with 200 sac string before	aly 500° of new 8 5 and comented with 7 " 0.1). grade "H" 17 off in the Red Sand casing will be run ks coment. Also, w commuting the 52" of

#.



4547--Artesia Printing Co.



30-015-03862