

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-G-3
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 0610

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection

2. NAME OF OPERATOR

Kay Jay Oil Co. ✓

3. ADDRESS OF OPERATOR

P.O. Box 3565 Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

1650' FSL-1650' FEL-Sec.16-T16S-R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

3757' GL

7. UNIT AGREEMENT NAME

SW Henshaw Premier Unit

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

West Henshaw Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 16-T16S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to P & A subject waterflood injection well due to termination of water injection as follows:

1. Set CIBP @ 2550' w/15 sx. cement on top of plug.
2. Spot 25 sx. cement plug 2050' - 1800' (Top of Queens)
3. Pressure test casing to determine any additional repair plugs.
4. Perforate @ 1200' & spot 35 sx. cement plug. (100' inside & 100' outside). WOC & tag plug.
5. Perforate @ 500' & spot 35 sx. cement plug. (100' inside & 100' outside.) WOC & tag.
6. Set 10 sx. surface plug.
7. Install dry hole marker and restore location.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side