

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Water Injection Well

2. Name of Operator

Kay Jay Oil Company ✓

3. Address and Telephone No.

P.O. Box 3788, Midland, TX 79702 (915) 684-9588

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL/660' FWL  
Sec. 17-T16S-R30E

(SJS)

RECEIVED

SEP 24 1991

O. C. D.

ARTESIA OFFICE

5. Lease Designation and Serial No.

NM 0560379

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

S.W.Henshaw Premier Unit

8. Well Name and No.

Well #11

9. API Well No.

10. Field and Pool, or Exploratory Area

West Henshaw Grayburg

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1-16-86 1. Set 7" CIBP @ 2600' - Spot 15 sxs. on Top  
1-17-86 2. Spot 25 sxs. @ 1950' - 1800'  
1-20-86 3. Test Casing - Perf. @ 1200' - Squeeze 45 sxs. - Tag. @ 1096'  
1-20-86 4. Perf. @ 600' - Squeeze 45 sxs. - Tag. @ 601'  
1-21-86 5. Squeeze 55 sxs. @ 600' - Tag. @ 397'  
1-21-86 6. Spot 10 sxs. @ surface  
All plugs set thru tubing  
Hole circulated with Mud  
Class C cement used

Approved by \_\_\_\_\_ of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

Post ID-2  
10-4-91  
P+H

14. I hereby certify that the foregoing is true and correct

Signed Shirley Rose Title Agent Date 9/18/91

(This space for Federal or State office use)

Approved by Shirley Rose Title ARTESIA ENGINEER Date 9/23/91  
Conditions of approval, if any: