

(SUBMIT IN TRIPLICATE)

Artesia, N. M.

Land Office

10-028940

Lease No.

U. S. Co. #72016

Federal Virginia F.
Carpenter et vir.UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

HOEBS OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas July 18

44

19

Well No. 1 is located 1980 ft. from N line and 1980 ft. from E line of sec. 20

SE/4 of NE/4 of Sec. 20

16-8

30-2

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Square Lake Wildcat

344

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 3775 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well plugged and abandoned as follows: Filled hole with mud-laden fluid from 3518-3370'. Cemented with 35 sacks Inceor from 3370-3330'. Filled hole with mud-laden fluid from 3330-2250'. Put in cement plug of 25 sacks Inceor from 2250-2150'. Unscrewed 7" casing, recovering 1764', leaving 437' in hole. Filled hole with mud-laden fluid from 2150-1175'. Cemented hole with 55 sacks Inceor from 1175-1065'. Filled hole with mud-laden fluid from 1065-640'. Cemented hole with 45 sacks Inceor from 640-545'. Tested hole by bailer at 545', found hole dry. Shot 10-3/4" casing at 545' recovering 160' leaving 341' in hole. Filled hole with mud-laden fluid from 545' to 30'. Spotted cement plug with 28 sacks Inceor from 30' to 5'. Filled cellar with cement and set up regulation marker in cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining CompanyAddress Box 1600Midland, Texas

By

Title Division Chief Clerk