

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 1359, Artesia, NM 88211-1359 (505) 748-1288

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec.27 T-16-S R-30-E 660' FSL & 1980' FEL

5. Lease Designation and Serial No.

NM-12764

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Nunlee Fed #2

9. API Well No.

10. Field and Pool, or Exploratory Area

Square Lake G-SA

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Spot 40 sacks cement, plug @ 2800' Tag cement top @ 2646'
- 2) Load hole with mud
- 3) Perforate 7" casing @ 8-5/8 shoe 2372' Squeeze with 50 sacks cement W.O.C. Tag cement top @ 2258'
- 4) Perforate 7" & 8-5/8" @ base of salt 1270' Squeeze with 60 sacks cement W.O.C. Tag cement top @ 1107'
- 5) Perforate 7" & 8-5/8" @ 603' 10" shoe Squeeze with 75 sacks cement W.O.C. Did not tag any cement, Resqueeze with 75 sacks cement W.O.C. Tag cement top @ 494'
- 6) Perforate 7" & 8-5/8" @ 60' Attempt to circulate with 30 sacks-unable W.O.C. Tag cement @ 65' circulated cement to surface between 7" & 8-5/8" with 94 sacks leaving 7" full.
- 7) Job Completed 1/24/96

APR 26 1996

OIL CON. DIV.
DIST. 2

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

Pat ID-2
5-10-96

P&A

14. I hereby certify that the foregoing is true and correct

Signed

Educa A. Cook

Title

District Secretary

Date

1-24-96

(This space for Federal or State office use)

Approved by

(ORIG. SCD.) JOE G. LARA

Title

PETROLEUM ENGINEER

Date

4/19/96

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side