

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Federal Bogle NM-01146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR HUMBLE OIL & REFINING COMPANY		8. FARM OR LEASE NAME Federal Bogle Federal	
3. ADDRESS OF OPERATOR Box 2100, Hobbs, New Mexico 88240		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' North of South Line, 660' East of West Line, Section 30, T-16-S, R-30-E, Eddy County, New Mexico		10. FIELD AND POOL, OR WILDCAT Square Lake SF	
14. PERMIT NO. -		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3716 D.F.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 30, T-16-S, R-30-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged and abandoned. Plugs set as follows.

Plug #1 from 2773' to 2580' with 25 sacks cement.

Plug #2 from 1200' to 1100' with 25 sacks cement.

Plug #3 from 565' to 465' with 25 sacks cement.

Plug #4 from 30' to surface with 10 sacks cement.

Shot and pulled 5-1/2" casing from 1190'.

Mud laden fluid between plugs.

Dry hole marker installed as per N.M.O.C.C. requirements.

When the location is cleaned and leveled the U.S.G.S. will be notified.

RECEIVED
NOV 15 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

SEP 20 1966

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

SIGNED:

E. S. DAVIS

TITLE

District Adm. Supvr.

DATE

November 11, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
SEP 1 1966R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

887-881

RECEIVED

APR 10 1964

U.S. DEPT. OF THE INTERIOR

COPIES DESTROYED - E 2 DEVAL

RECEIVED