

c/sf

Form 9-331
Dec. 1973

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED BY

APR 20 1987

Form Approved.
Budget Bureau No. 42-R1424

O. C. D. LEASE
ARTESIA, OFFICE NM

02425

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Injection Well

2. NAME OF OPERATOR

J. Cleo Thompson

3. ADDRESS OF OPERATOR

P.O. Box 6445 Odessa, Texas 79767

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL + 660' FWL of Sec. 33

AT TOP PROD. INTERVAL: 2808'

AT TOTAL DEPTH: 2881'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

Plug & Abandon

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Square Lake Unit

8. FARM OR LEASE NAME

Tract 2

9. WELL NO.

8

10. FIELD OR WILDCAT NAME

Square Lake (GB. SA.)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33 T16S R30E

12. COUNTY OR PARISH

EDDY

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3729' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

(1) C.I.B.P. @ 2675' w/1050' cmt on top.

(2) Perf. @ 2130' Set R.P. @ 1900' Pump 50 sx. cmt. leave 200' of cmt. over perfs. (Queens & Seven Rivers)

(3) Perf @ 1180' set R.P. 1000 pump 50 sx. cmt. leave 100' over perfs. (Base Of Salt)

(4) Perf. @ 594' (50' above salt) Circulate cmt. to surface and leave 5 1/2 csg. full.

(5) Cut csg. 3' below ground level. Set surface marker.

(R.P. stands for retrievable packer.)

Johnson 101 S

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED

Amador P. R. Jr.

TITLE

Production Foreman

DATE

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APR 16 1987

CARLSBAD, NEW MEXICO

Post ID-2
4-21-87
P.A.