

ckf

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED BY

APR 15 1987

O. C. D.

ARTESIA, OFFICE

5. LEASE

L. C. 063926

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Square Lake Unit

8. FARM OR LEASE NAME

WSLU Tract 7

9. WELL NO.

9-Y

10. FIELD OR WILDCAT NAME

Square Lake

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35 T-16s R-30 e

12. COUNTY OR PARISH

13. STATE

EDDY

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3760' GL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other WIW

2. NAME OF OPERATOR

J. Cleo Thompson

3. ADDRESS OF OPERATOR

P. O. Box 12577 Odessa, Texas 79768-2577

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 610 Fw1 1980 Fs1 of Sec. 35 T-16s R30e

AT TOP PROD. INTERVAL: 2975'

AT TOTAL DEPTH: 3182'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

TH-WIEW

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- (1) Set C. I. B. P. @ 2,950'. Dump 50' of cement on top. (Top perf. @ 2,975')
  - (2) Perf. @ 2,295'. Pump 50 sacks cement into perfs and leave 200' cement on top of perfs. CALC. T. O. C. 2,095' (Queens and Seven Rivers).
  - (3) Perf. @ 1,295' pmp 50 sacks cement into perfs and leave 100' cement on top of perfs. CALC. T. O. C. 1,195' (Base of salt 1,245').
  - (4) Perf. @ 520'. Circulate cement to surface (Top of salt 570').\*
  - (5) Cut csg. 3' below ground level and set surface marker and rehabilitate location as per BLM requirements.
- \*Set cement plug in 5 1/2" casing from 520' to surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Amos P. ...*

TITLE

*Production ...*

DATE

4-13-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

4-13-87

CONDITIONS OF APPROVAL, IF ANY:

FIELD.	WEST SQUARE LAKE	OPERATOR	J. CLEO THOMPSON	DATE	
LEASE	TRACT 7	WELL NO.	9X	LOCATION	610 E.W.L. 1980 F.S.L. SEC. 35 T16-R30

UNIT LETTER: L - NW 1/4 SW 1/4 SEC 35

Elev. 3760

LC 063926

8 5/8 " casing set at 133 ' with 30 sx of ✓ cement  
Hole size 10 " "

TOP OF SALT 570" PERF. AT 520 CIRC CEMENT TO SURFACE

10 " casing set at 570 with 50 sx of ✓ CEMENT

HOLE SIZE 12 1/4

CALC. TO.C. 1195

BASE OF SALT 1245" PERF. AT 1295 PUMP 50 SX CEMENT LEAVE  
100 FT INSIDE & OUTSIDE  
OF CASING

PERF. 1295

11-1-47 1705 FT OF 7" CASING WAS PULLED  
TOP OF 7 CASING AT 1705

CALC. TO.C. 2095

QUEENS + SEVEN RIVERS 2295  
PERF. 2295 50 SX. LEAVE 800 FT. OF CEMENT INSIDE OF CAS.

7 " casing set at 2265 ' with 100 sx of ✓ cement

Total Depth        ' Hole size 8 3/4 "

TOP PERF. AT 2975, SET C.I.R.P. AT 2950 WITH 50" OF CEMENT TO TOP OF C.I.R.P.

5 1/2 casing set at 3182 WITH 170 SX OF ✓ CEMENT

TOTAL DEPTH 3182 HOLE SIZE 7 7/8