

2/6f

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. ☐ oil well ☐ gas well ☐ other Water Injection Well

2. NAME OF OPERATOR
Mobil Producing TX. & N.M. Inc.

3. ADDRESS OF OPERATOR
Nine Greenway Plaza,
Suite 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980'FWL & 2310'FSL S10,T16S,R31E
AT TOP PROD. INTERVAL: Same as surface
AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) _____

SUBSEQUENT REPORT OF RECEIVED

SEP 29 '88

O. C. D.
ARTESIA, OFFICE

5. LEASE
NM-26218 026418

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Northeast Square Lake Premier Unit

8. FARM OR LEASE NAME

9. WELL NO.
27

10. FIELD OR WILDCAT NAME
North Square Lake, G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T-16S, R-31E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4191 GR, 4199 DF, 4202 KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

06/28/84 MIRU Mayo Marrs csg pulling ut, dug out cellar, notified BLM.

06/29- Rel pkr @ 3631, POH w/pkr, laying down 2-3/8 cmt lined tbg, WIH w/

07/01/84 cmt ret on tbg to 3600, displ csg w/9.5# mud laden fluid, cmt sqz
Premier perfs 3676-3738 w/30x Class C cmt, cap ret w/5x cmt.

07/02/84 Mayo Mars perf 4-1/2 csg w/4 holes @ 2230, RIH w/ pkr to 1700, sqzd
perfs w/35x Class C Neat cmt, TOC @ 2150, POH w/ pkr, Mayo perf 4-1/2
csg w/4 holes @ 850, cmt down 4-1/2 csg w/85x Class C Neat cmt, left
csg full of cmt, displ 35x out csg perfs @ 850, notified BLM.

07/03/84 Tag TOC @ 30', cut off wellhead, weld on plate, sqz 30x Class C cmt
down csg annl from surface to 30' and out holes in csg, cmt @ surface,
install well marker, RD & rel Mayo Marrs Csg Pullers @ 3 PM.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paula W. Collins TITLE Authorized Agent DATE 07/16/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9-28-88

CONDITIONS OF APPROVAL IF ANY:

Per Mike S. Field report
8-27-84

10-26-84
P&H

Approved as to correctness of the well bore.
Liability on the well is assumed until
surface reservoir is established.

*See Instructions on Reverse Side