

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**

Lease No. **029471**

Unit **"J"**

Unit **13 1944**

RECEIVED

HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL..... <input checked="" type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas October 10, 1944

S. M. Compton
Well No. **2** is located **1980** ft. from **S** line and **1980** ft. from **E** line of sec. **17**

N. 1/4 Sec. 17 **16-S** **31-E** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **Eddy** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3996** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

(See Attached Sheet)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **The Texas Company**

Address **Box 1270**

Midland, Texas

By _____

Title **District Superintendent**

Total Depth, 3512' - Line
10-3/4" casing cemented at 753' with 50 sacks.
8-5/8" casing mudded at 2691'.

We submit the following for your approval as to our method of plugging and abandoning this well.

Pull all 8-5/8" casing. Will attempt to part and pull approximately 500' of 10-3/4" casing. Hole will be filled with heavy mud, with the following cement plugs spotted: 30 sacks, 2985' to approximately 2885'; 30 sacks, 2690' to approximately 2630'; 20 sacks, 1670' to approximately 1630' (at base of salt); and 20 sacks, 780' to approximately 740' (in the anhydrite at top of salt). The required 4" pipe marker extending 4' above ground will be cemented in the top of the hole with 20 sacks. All mud and cement plugs will be pumped in through tubing.

This request is due to the fact that there were no indications of oil, gas or water below 2940' to total depth, 3512', and a test of the gas encountered at 2930' to 2940' indicated approximately 220 MCF per day and therefore is not commercial.

This confirms telephone conversation and approval of your office several days prior to the date of this report. Filing this report has been delayed, pending the decision of our management to plug and abandon this well.

