

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM L CONS COMMISSION
Drawer DD
Artesia, NM 88210
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Mack Energy Corporation

3. Address and Telephone No.
P.O. Box 960, Artesia, New Mexico, 88211-0960

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 19 T-16-S R-31-E 1980' FSL & 1660' FWL

OIL CON. DIV.
DIST. 2

5. Lease Designation and Serial No.
NM-016803

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Carper Fed #2

9. API Well No.
30-015-04855

10. Field and Pool, or Exploratory Area
Square Lake GB SA

11. County or Parish, State
Eddy, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Spot 14 sacks cement on top of CIBP at 3000'
2. Load hole with mud
3. Perforate casing at base of salt 1477'; squeeze with 30 sacks cement; wait on cement; tag 1348'
4. Perforate casing at top of salt 540;; squeeze with 60 sacks cement; wait on cement; tag cement top at 318'
5. Perforate casing at 60';; circulate cement to surface with 30 sacks cement between 5-1/2" 8-3/8" casing, leaving 5-1/2" full
6. Job completed 6-9-95

Per ID-2
8-18-95
P417

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the foregoing is true and correct

Signed [Signature] Title _____

(This space for Federal or State office use)

Approved by [Signature] Title PETROLEUM ENGINEER

Conditions of approval, if any:

Date 6-9-95

Date JUL 26 1995

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side