

**APPROVED****MAR 29 1963**  
**RONNIE E. SHOOK**  
**ACTING DISTRICT ENGINEER**

(SUBMIT IN TRIPLICATE)

**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**Land Office \_\_\_\_\_  
Lease No. 16-355302 (b)  
Unit -0-**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			
<u>Fracture</u>	<u>XX</u>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. Johnson is located 500 ft. from NW line and 100 ft. from E line of sec. 25  
3/4 14/4 Sec. 25 14S 31E P 1S  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Square Lake Ady New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to sandrill perforations from 5047-51 and spot 100 gallons acid on bottom, then run packer and fracture Lovington with 20,000 gallons water and 15,000 pounds sand. Well will then be put back on injection.

**RECEIVED****APR 1 1963****G. C. C.**  
**ARIZONA, OFFICE**

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Newmont Oil CompanyAddress 10414 MilviaArtesia, New MexicoORIGINAL SIGNED BY  
**H. J. LEDBETTER**

By \_\_\_\_\_

Title Superintendent