-	مثنام	H	81	
	/Maa	- 14	ŭ.	

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

•		*
Land Office	.Iaa	Cruces
Lease No. Q	6286	5

Budget Bureau Ne. 41-3388.1. Approval expires 11-30-38.

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
OTICE OF INTENTION TO CHANGE PLANS		
TICE OF INTENTION TO TEST WATER SHUT-OFF	I II	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	1)i	
OTICE OF INTENTION TO SHOOT OR ACIDIZE	; II	
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	1
OTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	February 21	, 19. l.2
30 16 (TER)	inty of Subdivision) (State or Territory	
DET	TAILS OF WORK	
nto names of and expected depths to objective sands; shorting points, and	r since, weights, and lengths of proposed casings; indicate mud- all other impertant proposed work)	
above-described well has been posted with 50 sacks of mud and 10 in the hole and set a control with 50 sacks of mud and 10 in the hole and set a control with 50 sacks of mud and 10 in the hole and set a control with 50 sacks of mud and 10 in the hole and 10 in		oks of mid if coment. If coment. It is the coment of the c
above-described well has been placed with 50 sacks of mud and 10 and sacks of cement, filled holdement. We recovered approximate	values, weights, and lengths of proposed casings; indicate much all other important proposed work) lugged and abandoned. We put 20 sament bridge at 2600' with 5 sacks of sacks of cement and set a cement breaks of cement and set a cement breaks of cement and set a mark	oks of mid if coment. If idea at 4000 ker with 5 s f 2" tubing.
above—described well has been placed with 50 sacks of mud and 10 and 10 sacks of cement, filled hold ment. We recovered approximate the sacks of approximate the sacks of sacks of approximate t	values, weights, and lengths of proposed casings; indicate much all other important proposed work) lugged and abandoned. We put 20 sament bridge at 2600' with 5 sacks of sacks of cement and set a cement breaches to surface with mud and set a may ely 2000'of 52" casing and 3000'o	cks of mid if coment. It idge at 400 ker with 5 kg 2 tubing.
above-described well has been plattom of the hole and set a consideration of the hole and set a consid	wines, weights, and lengths of proposed casings; indicate much all other impertant proposed work) lugged and abandoned. We put 20 sament bridge at 2600' with 5 sacks of sacks of cement and set a cement bre to surface with mud and set a marely 2000 of 5% casing and 3000 of 1000	cks of mid if coment. It idge at 4000 ker with 5 s f 2" tubing.
above—described well has been plattom of the hole and set a consideration of the hole and set a consid	wines, weights, and lengths of proposed casings; indicate much all other impertant proposed work) lugged and abandoned. We put 20 sament bridge at 2600' with 5 sacks of sacks of cement and set a cement bre to surface with mud and set a marely 2000 of 5½ casing and 3000 of 5½ casing an	cks of mid if coment. It idge at 4000 ker with 5 s f 2" tubing.

U. S. GOVERNMENT PRINTING OFFICE 16-0487-8