Form 9-881 a (Feb. 1951)

Budget Bureau No. 42-R358.4. Form Approved,

Lease No. 10-060545

UNITED STATES **DEPARTMENT OF THE INTERIOR**

(SUBMIT IN TRIPLICATE)

GEOLOGICAL SURVEY

IOTICE OF INTENTION TO DRILL		
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF	
	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZII	NG
OTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	yv -
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPA	IR
OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	· · · · · · · · · · · · · · · · · · ·
OTICE OF INTENTION TO PULL OR ALI'ER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	January 23,	19. ⁶³
Sruning Unit ll No. 30. 1 is located 1930 ft. i	from $\begin{bmatrix} N \\ S^N \end{bmatrix}$ line and $\begin{bmatrix} 660 \\ W \end{bmatrix}$ ft. from $\begin{bmatrix} 18 \\ W \end{bmatrix}$ line	of sec
(4 Sec. and Sec. No.) (Twp.))1. YET	
		. – П
. guare lake (Field) (Co	DEG	by A.E.
e elevation of the derrick floor above se	ea level isft.	2 5 153 3
DE	ETAILS OF WORK JAN '	.
, 370' of 4." liner. set at 340	now sizes, weights, and lengths of proposed casings; indicated all other important proposed work)	ar gerent.
tent and cleaned out to TD 3399/6-30, 3566-70, 3550-62, 3227-500. Spotted 150 gallons 15% actions elick water and 15,000/2 20-40- sand. From 20-40-80. State 15 between 485 bbls water let 15 be	if and comented with 50 sacks regular. San sand drill tool and made 2001, 5525-57, 5179-35. Set packers id on formation. Fraced levington to 40 sand. Fraced Franker with 10 raced Fetex with 10,000 gallons slinears at 2150.	ar cement.) minute cut: at 52244, 53 ad th 20,000
ment and cleaned out to TD 3399 76-30, 3566-70, 5553-62, 3227-53 10. spotted 150 gallons 15% ac	if and comented with 50 sacks regular. San sand drill tool and made 2001, 5525-57, 5179-35. Set packers id on formation. Fraced levington to 40 sand. Fraced Franker with 10 raced Fetex with 10,000 gallons slinears at 2150.	ar cement.) minute cut: at 52244, 53 ad th 20,000
sent and cleaned out to TD 3399. [6-30, 3566-70, 5553-62, 3227-5] [10. spotted 150 gallons 15% accilions elick water and 15,000; 20ter and 7,500; 20-40-sand. [10. spotted 150; 20-40-sand. [11. took 485 bbls water let 16 hejection the following day was 4	if and comented with 50 sacks regular. San sand drill tool and made 2001, 5525-57, 5179-35. Set packers id on formation. Fraced levington to 40 sand. Fraced Franker with 10 raced Fetex with 10,000 gallons slinears at 2150.	ar cement. minute outs at 32247, 53 at th 20,000 ,000 gallow
tent and cleaned out to TD 3099. (6-30, 3566-70, 5553-62, 3227-5. (0. spotted 150 gallons 15% actions elick water and 15,000, 20 ter and 7,500, 20-40 sand. (1) took 485 bbls water let 16 he jection the following day was 4	4 and comented with 50 sacks regular sand drill tool and made 20 (1, 5525-57, 5175-55. Set packers id on forsation. Fraced Levington 10-40 sand. Fraced Presier with 16 raced Fetax with 10,000 gallons slinears at 2150.	ar cement. minute outs at 32247, 53 at th 20,000 ,000 gallow
tent and cleaned out to TD 3399 (6-30, 3566-70, 3559-62, 3227-5) (0. spotted 150 gallons 15% actions elick water and 15,000, 20 for and 7,500, 20-40 sand. From 20-40 sand. It took 485 bbls water let 16 he jection the following day was 4 understand that this plan of work must receive appropriately water that the plan of work must receive ap	4 and comented with 50 sacks regular sand drill tool and made 20 (1, 5525-57, 5175-55. Set packers id on forsation. Fraced Levington 10-40 sand. Fraced Presier with 16 raced Fetax with 10,000 gallons slinears at 2150.	ar cement. minute outs at 32247, 53 at th 20,000 ,000 gallow
tent and cleaned out to TD 3099/6-30, 3566-70, 3550-62, 3227-500. Spotted 150 gallons 15% actions elick water and 15,000# 20 ter and 7,500# 20-40- sand. From 20-40 sand. It took 485 bbls mater lat 16 he jection the following day was 4 understand that this plan of work must receive appropriate the same of	4 and comented with 50 sacks regule. San sand drill tool and made 20 (1, 5525-57, 517)-35. Set packers aid on forsation. Fraced levington 10-40 sand. Fraced Premier with 10 raced Fetax with 10,000 gallons slinears at 2150. 195 bbls at 2150/	ar cement. minute outs at 32247, 53 at th 20,000 ,000 gallow