

06-111

321 Ward Building
Alameda, New Mexico

October 11, 1944

Mr. J. H. Palmer
Ward Building
Alameda, New Mexico

Mr. J. H. Palmer

Reference is made to your letter of October 11, 1944, regarding the location of the building at Alameda, New Mexico, located in Sec. 10, T. 1N, R. 1E, S. 1E, and the location of the building at Alameda, New Mexico, located in Sec. 10, T. 1N, R. 1E, S. 1E.

Reference is made to your letter of October 11, 1944, regarding the location of the building at Alameda, New Mexico, located in Sec. 10, T. 1N, R. 1E, S. 1E, and the location of the building at Alameda, New Mexico, located in Sec. 10, T. 1N, R. 1E, S. 1E.

Very truly yours,



J. H. Palmer

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 16 01563

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 23, 1934

Well No. 8 is located 1900 ft. from N line and 1870 ft. from W line of sec. 36
16 S. T. 2 E. N.M.P.M.
 (Sec. and Box No.) (Twp.) (Range) (Mention)
Alamosa Doña Ana New Mexico
 (Name) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State nature of and reported depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Augmentation is made to drill on the above location to a maximum depth of approximately 3000 feet under the following program:
 1. Cement 5" casing at an approximate depth of 900' in the sandstone immediately above the salt with 50 sacks of cement preceded by commercial mud circulated to surface.
 2. Set 7" casing at approximately 1500 feet and circulate commercial mud to surface for water shut-off.
 3. Cement 5" casing at an approximate depth of 2500' with 100 sacks of cement preceded by commercial mud circulated to surface.
 4. Run electrical log from the 5" casing to surface.
 Total depth.

I understand that this plan of work must receive approval in writing by the Geological Survey before commencing operations.

Company WHEELEY & WOODWARD
 Address 2925 - 45th St. N.W.
Washington, D. C.

By Wheley & Woodward
 Title owner

