

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 062845

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	☒
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 9, 1948

Geo. Ets Woodward 1980
Well No. 2 is located 440 ft. from N line and 440 ft. from W line of sec. 30

Range 30 16 South 11 East N.M.P.M.
(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Square Lake Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and suggested depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above described well has been plugged and abandoned. A cement bridge was set at 2970' with 10 sacks of cement in bottom of 5 1/2" casing. We mudded with 10 sacks of mud. A cement bridge was set in bottom of 8 1/2" casing at 530' with 10 sacks of cement. Marker was cemented with 5 sacks of cement. We recovered approximately 1990' of 5 1/2" casing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.


Company Brewer Drilling Company

Address Box 544, Artesia, N. M.

By

[Signature]

Title Partner



LOCATE WELL CORRECTLY

LOG OF OIL OR GAS WELL

Company **Hoke L. Woodward**

Washington

Lessor or Tract **ETZ** Field **Square Lake** State **New Mexico.**
Well No. **2** Sec. **30** T. **16S** R. **31E** Meridian **NMPM** County **Eddy**
Location **1980** ft. **X** of **N** Line and **1670** ft. **X** of **E** Line of **Sec. 30** Elevation

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed **Paton Bros.**

Date **January 10, 1945**

By **Contractor**

The summary on this page is for the condition of the well at above date.

Commenced drilling **Oct. 31st** to **4** Finished drilling **January 1st,** to **45**

OIL OR GAS SANDS OR ZONES

(See logs by G.)

No. 1, from **30** to **3073** No. 4, from **3073** to **3112**
No. 2, from **3112** to **3127** No. 5, from **3127** to **3140**
No. 3, from **3140** to **3150** No. 6, from **3150** to **3160**

IMPORTANT WATER SANDS

No. 1, from **2410** to **2420** No. 3, from **2420** to **2430**
No. 2, from **2430** to **2440** No. 4, from **2440** to **2450**

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Other notes	Depth	Purpose
8"	23	8	4 1/2 inch 245'	245'	Texas			
8"	20	"	4 1/2 inch 2470'	2470'	water			
8"	14	"	4 1/2 inch 2950'	2950'				

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Water used	Mud gravity	Volume of mud used
8"	525	50 sacks	1 bbl.		
7"	2470		1 bbl.		
5"	2950	1 bbl.			

Heaving pump Material

Adapters Material

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth	Other notes
3 1/2		Zero Time Bomb 100	1/3	'45	3063-3134	7138

TOOLS USED

Rotary tools were used from **top** feet to **3160** feet, and from **3160** feet to **3170** feet
Cable tools were used from **top** feet to **3160** feet, and from **3160** feet to **3170** feet

Bates

Put to producing **January 1,** to **1945**

The production for the first 24 hours was **75** barrels of fluid of which **100** was oil

FOLD MARK