une 1990) EEEE DEPARTMEN BUREAU OF 1 SUN DRONOTICES Do not use this for proposals to dr	TED STATES IT OF THE INTERIOR LAND MANAGEMENT AND REPORTS ON WELLS ill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	NM OIL CONS COMMISSION Drawer DD Artes FORM MPROVEDTO Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NMLC029431 6. If Indian, Allottee or Tribe Name
AREA SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
Type of Well Image: Second		8. Well Name and No.
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471)		Vickers Federal #3
Address and Telephone No		30-015-04935
105 South 4th St., Artesia, NM 88210		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FEL of Section 30-T16S-R31E (Unit G, SWNE)		Square Lake G-SA 11. County or Parish, State
		Eddy Co., NM
2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	XX Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back NOV O	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
L.J Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	_ L Dispose Water (Note: Report results of multiple completion on Well
3. Describe Proposed or Completed Operations (Clearly state al	pertinent details, and give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Log form.)
Bob Fant, Engineer with Yates Lara with the BLM in Carlsbad plug and abandon well as is. 10-7-94 - Rigged up rotary win Pump through retainer. Mix ar Shut down. Holding 200 psi. with tubing. Nippled down BOF at 560'. TOOH with 14 joints Perforate 4 holes at 550'. Se through retainer. Mix and pum of retainer. Left 1 bb1 (42') Set 8-5/8" retainer at 200'. Mix and pump 110 sacks Class C casing full of cement from 250 marker. <u>PLUGGED AND ABANDONED</u> NOTE: BLM did not witness plu	Petroleum Corporation, received verbal and Tim Gumm with the OCD in Artesia, eeline. Set 5-1/2" cement retainer at ad pump 200 sacks Class C Neat cement a Sting out of retainer. Left 42' of ce and 5-1/2" Larking head. Pick up on of 5-1/2" 15.5# casing and overshot. t 8-5/8" cement retainer at 500'. TIH p 150 sacks Class C Neat cement at 3 B of cement on retainer. TOOH. Perfor TIH and sting into retainer. Pump 16 Neat cement. Circulate out 8-5/8" an '. Cut off 8-5/8" head. Installed re - FINAL REPORT. Plugging completed 0	<pre>960'. TIH with stinger. 960'. TIH with stinger. at 3 BPM at 400-500 psi. ement on retainer. TOOH 5-1/2". Release overshot TIH with 4" casing guns. With tubing. Pump BPM at 0 psi. Sting out rate 4 hole at 250'. bbls fresh water. Circulate. d surface and left 8-5/8"</pre>
4. I hereby certify that the foregoing is true and correct		<u>114</u> _
signed Tusley Tullen	Title Production Clerk	Oct. 12, 1994
(This space for Federal of State office use) Orig. Signed by Adam Salameh	Title	Date 11 17/94
Conditions of approval, if any:		

File 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.